



OAK BURGUNDY

Oak Burgundy is a classic floor, where the natural wood characteristics has been enhanced with microbevel and brushing topped with a natural oil

PRODUCT DETAILS		FACTS		TECHNICAL PROPERTIES		
Article Number	151N8AEKF0KW220	Wood Species	Oak	Moisture	EN13183	7%±2%
EAN Code	7393969041256	Design	1-strip	content		
Surface Treatment	Oil This floor should be oiled immediately after installation.	Grading	Lively	Minimun Mean Density kg/m³ >500 kg/m³		
		Range	Kährs Original	Reaction To Fire	EN13501-1	Dfl-s1
		Collection	European Naturals Collection	Formaldehyde	EN717-1	E1
Refining Treatment	Microbevelled 4-sided, Brushed	Natural/Stained	Natural	Emission Content PCP	CEN/TR14823	≤ 5 x 10-6n
Dimensions	2266 x 187 x 15 mm	Brinell Value	3,7	Breaking	EN1533	NPD
Weight per Package	21 kg	Joint	Woodloc® 5S	Strength	LIVIOSO	NID
Area per Package	2.5 m ²	Floor heating	Yes	N/mm²		
Area per pallet (m²)	0 m²	Wear-layer material	Hardwood	Thermal Conductivity	EN12664	0,14 W/mK
Package info	Packages may contain start and stop boards.	Core material	Pine/Spruce lamella	Thermal Resistance R-Value		.11 (m2K/W)
		Thickness	15 mm	Biological	EN350-2	Class 1
DETAIL DESCRIPTION		Installation method	Floating, Glue-down	Durability		
Naturally occuring wood colour variations allowed,				CARB2		Compliant

COLOUR CHANGE

numbers.

Some muting of colour variation to medium, straw brown.

from light to dark brown. The product includes large sound and black knots. Knots may vary in size and







Descriptions & Imagery

All samples, images and product description, plus photo and brochure specifications are there for the sole purpose of giving an approximate idea of the items described in them. They shall not form part of the contract or have any contractual force and should be viewed for illustrative purposes only. We cannot guarantee that your computer's display or the quality of the print will accurately reflect the colour of the products. Your product may vary slightly from the images within this literature.